

SPC

STONE PLASTIC COMPOSITE



FLOORING

We deliver high-performance solutions straight to your business, ensuring precise and efficient outcomes



- Waterproof
- Termite Resistant
- Scratch Resistant
- Wear Resistant
- Easy to Clean
- Stain Resistant
- Easy to Install
- Bacteria Free



SPC TERMURAH DI MALAYSIA



Page 4-10	THICKNESS	4MM
	SIZE	180MM X 1220MM 24SQFT @ 10PCS/BOX
	WEAR LAYER	12 MIL (0.3MM)
	PRICE	RM 2.49/SQFT RM 59.99 (MIN. 100 BOX) 10 PCS/BOX @ 24 SQFT



Page 11-19	THICKNESS	4MM
	SIZE	150MM X 600MM 24SQFT @ 24PCS/BOX
	WEAR LAYER	12 MIL (0.3MM)
	PRICE	RM 2.88/SQFT RM 69 (MIN. 100 BOX) 10 PCS/BOX @ 24 SQFT



Page 20-25	THICKNESS	5MM
	SIZE	183MM X 1220MM 24SQFT @ 10PCS/BOX
	WEAR LAYER	20 MIL (0.5MM)
	PRICE	RM 2.99/SQFT RM 72 (MIN. 100 BOX) 10 PCS/BOX @ 24 SQFT



Page 26-30	THICKNES S	5MM
	SIZE	183MM X 1220MM 24SQFT @ 10PCS/BOX
	WEAR LAYER	20 MIL (0.5MM)
	PRICE	RM 3.29/SQFT RM 79 (MIN. 100 BOX) 10 PCS/BOX @ 24 SQFT



Page 31-35	THICKNESS	7MM
	SIZE	183MM X 1220MM 24SQFT @ 10PCS/BOX
	WEAR LAYER	20 MIL (0.5MM)
	PRICE	RM 4.30/SQFT RM 103 (MIN. 100 BOX) 10 PCS/BOX @ 24 SQFT

FLOORING ACCESSORIES

Page 36-43



SPC FLOORING

SPC flooring is a modern, highly durable flooring option made from stone plastic composite (SPC). It combines the strength of stone with the flexibility of PVC, making it both tough and versatile. Made from calcium carbonate powder and PVC, SPC flooring is produced using a hot roller press method. It comes in 4mm, 5mm, and 7mm thicknesses, with an easy interlocking system for quick installation. The surface is protected with a wear layer and a UV coating for added durability. Ideal for both residential and commercial spaces, SPC flooring offers a low-maintenance, cost-effective solution that delivers long-lasting performance.

Durability

SPC flooring durability depends on the thickness of the wear layer applied onto the decorative film. Generally the thicker the wear layer, the more durable the flooring against wear and tear.

8 MIL
Wear Layer

suitable for all residential up to moderate commercial area

12 MIL
Wear Layer

suitable for all residential up to heavy commercial area

20 MIL
Wear Layer

suitable for all residential up to heavy commercial area



- 1 UV Layer
- 2 Wear Layer
- 3 Decorative Layer
- 4 SPC Rigid Board

Advantages



Waterproof



Termite Resistant



Scratch Resistant



Wear Resistant



Easy to Clean



Stain Resistant



Easy to Install



Bacteria Free

Benefit

- ✓ Easy to maintain
- ✓ Can be used immediately
- ✓ Low installation cost



L I O N

4MM SPC CLICK

WEAR LAYER 12 MIL (0.3MM)



HARGA DIRECT KILANG

RM2.49
/sqft

HARGA SIAP PASANG

RM3.98
MINIMUM 800 SQFT

RM4.25
MINIMUM 350 SQFT

10 PCS / BOX @ 24 SQFT

RM59.99
(RM2.49/SQFT)
MINIMUM 100 BOX

RM63
(RM2.63/SQFT)
MINIMUM 50 BOX

RM66
(RM2.75/SQFT)
NO MINIMUM QUANTITY

Size	Thickness	Material	Edge Finish	Wear Layer	Joint System	Packing Content	Area Suitability
180mm x 1220mm	4mm	100% Virgin Material	Micro Bevel	12 MIL (0.3MM) + UV Coating	Interlocking Unilin Click	24 sqft/ 10 pcs/box	Indoor residential up to heavy commercial area



CP432



CP427



CP422



CP428



CP429



CP417



CP404



CP438



CP439

[CLICK HERE TO WATCH VIDEO](#)





L I O N

4MM SPC CLICK

WEAR LAYER 12 MIL (0.3MM)



HARGA DIRECT KILANG

RM2.49
/sqft

HARGA SIAP PASANG

RM3.98
MINIMUM 800 SQFT

RM4.25
MINIMUM 350 SQFT

10 PCS / BOX @ 24 SQFT

RM59.99
(RM2.49/SQFT)
MINIMUM 100 BOX

RM63
(RM2.63/SQFT)
MINIMUM 50 BOX

RM66
(RM2.75/SQFT)
NO MINIMUM QUANTITY

Size	Thickness	Material	Edge Finish	Wear Layer	Joint System	Packing Content	Area Suitability
180mm x 1220mm	4mm	100% Virgin Material	Micro Bevel	12 MIL (0.3MM) + UV Coating	Interlocking Unilin Click	24 sqft/ 10 pcs/box	Indoor residential up to heavy commercial area



[CLICK HERE TO WATCH VIDEO](#)





L I O N

4MM SPC CLICK

WEAR LAYER 12 MIL (0.3MM)



HARGA DIRECT KILANG

RM2.49
/sqft

HARGA SIAP PASANG

RM3.98
MINIMUM 800 SQFT

RM4.25
MINIMUM 350 SQFT


10 PCS / BOX @ 24 SQFT

RM59.99
(RM2.49/SQFT)
MINIMUM 100 BOX

RM63
(RM2.63/SQFT)
MINIMUM 50 BOX

RM66
(RM2.75/SQFT)
NO MINIMUM QUANTITY

Size	Thickness	Material	Edge Finish	Wear Layer	Joint System	Packing Content	Area Suitability
180mm x 1220mm	4mm	100% Virgin Material	Micro Bevel	12 MIL (0.3MM) + UV Coating	Interlocking Unilin Click	24 sqft/ 10 pcs/box	Indoor residential up to heavy commercial area



[CLICK HERE TO WATCH VIDEO](#)





L I O N

4MM SPC CLICK

WEAR LAYER 12 MIL (0.3MM)



HARGA DIRECT KILANG

RM2.49
/sqft

HARGA SIAP PASANG

RM3.98
MINIMUM 800 SQFT

RM4.25
MINIMUM 350 SQFT

10 PCS / BOX @ 24 SQFT

RM59.99
(RM2.49/SQFT)
MINIMUM 100 BOX

RM63
(RM2.63/SQFT)
MINIMUM 50 BOX

RM66
(RM2.75/SQFT)
NO MINIMUM QUANTITY

Size	Thickness	Material	Edge Finish	Wear Layer	Joint System	Packing Content	Area Suitability
180mm x 1220mm	4mm	100% Virgin Material	Micro Bevel	12 MIL (0.3MM) + UV Coating	Interlocking Unilin Click	24 sqft/ 10 pcs/box	Indoor residential up to heavy commercial area



CP401A



CP401B



CP402A



CP402B



CP424



CP425



CP437

[CLICK HERE TO WATCH VIDEO](#)





L I O N

4MM SPC CLICK

WEAR LAYER 12 MIL (0.3MM)



HARGA DIRECT KILANG

10 PCS / BOX @ 24 SQFT

RM2.49
/sqft

RM59.99
(RM2.49/SQFT)
MINIMUM 100 BOX

HARGA SIAP PASANG


RM3.98
MINIMUM 800 SQFT

RM63
(RM2.63/SQFT)
MINIMUM 50 BOX

RM4.25
MINIMUM 350 SQFT

RM66
(RM2.75/SQFT)
NO MINIMUM QUANTITY

STUCTURE DIAGRAM



4MM VIRGIN SPC INTERLOCKING FLOORING

SPC Flooring provides exceptional dimensional stability, superior performance, waterproofing, and impressive indentation resistance due to its high density - core



WATERPROOF

STAIN RESISTANT

TERMITE RESISTANT

NOISE RESISTANT

SCRATCH RESISTANT

FLAME RETARDANT

AFFORDABLE

VARIETY OF DESIGN OPTIONS

PET-FRIENDLY



L I O N

4MM SPC CLICK

WEAR LAYER 12 MIL (0.3MM)



HARGA DIRECT KILANG

RM2.49
/sqft

HARGA SIAP PASANG

RM3.98
MINIMUM 800 SQFT

RM4.25
MINIMUM 350 SQFT


10 PCS / BOX @ 24 SQFT

RM59.99
(RM2.49/SQFT)
MINIMUM 100 BOX

RM63
(RM2.63/SQFT)
MINIMUM 50 BOX

RM66
(RM2.75/SQFT)
NO MINIMUM QUANTITY

METHOD OF INSTALLATION



SIZE

180MM X 1220MM

WEAR LAYER

12 MIL (0.3MM)

COVERAGE PER BOX

24 SQFT (10 PCS)

THICKNESS



[CLICK HERE TO WATCH VIDEO](#)

VERIFIED BY :





L I O N

4MM SPC CLICK

WEAR LAYER 12 MIL (0.3MM)



HARGA DIRECT KILANG

RM2.49
/sqft

HARGA SIAP PASANG

RM3.98
MINIMUM 800 SQFT

RM4.25
MINIMUM 350 SQFT

10 PCS / BOX @ 24 SQFT

RM59.99
(RM2.49/SQFT)
MINIMUM 100 BOX

RM63
(RM2.63/SQFT)
MINIMUM 50 BOX

RM66
(RM2.75/SQFT)
NO MINIMUM QUANTITY

PRODUCT DETAIL

Material	100% Virgin Material
Size	180mm x 1220mm
Thickness	4mm
Wear Layer	12 mil (0.3 mm)
Treatment	UV Coating (Two Coats)
Click & Lock System	Unilin
Wear Resistant	24 sqft/10 pcs per box
Packaging	Group T
4 Side Edges	Micro Bevel
Martindale Abrasion Test	EN 16094 (MSR-B2)
Castor Wheel Resistant	BS EN iso 4918:2021 (PASS)
Impact Resistant	BS EN 13329:2016+A2:2021 Annex H (BIGBALL>1000MM)
Reaction To Fire Behavior	ASTM E648-194a (CLASS 1)
Slip Resistance	DIN 51130-2004 (R10)
Emission of Formaldehyde	DIN717-2 (NOT DETECTED)
Residual Vinyl Chloride Monomer	EN ISO 6401-2008 (<0.5 MG/L)
VOC Test	GB 18581-2020 (PASS)
Phthalate Test	EN 14372 (PASS)
Prohibited Heavy Metal	ICP-OES (PASS)

CHEVRON HERRINGBONE 4MM



LUXURY SPC FLOORING

WEAR LAYER 12 MIL (0.3MM)



HARGA DIRECT KILANG

RM2.88
/sqft

HARGA SIAP PASANG

RM4.45
MINIMUM 800 SQFT

RM4.78
MINIMUM 350 SQFT

24 PCS / BOX @ 24 SQFT

RM69
(RM2.88/SQFT)
MINIMUM 100 BOX

RM74
(RM3.08/SQFT)
MINIMUM 50 BOX

RM79
(RM3.28/SQFT)
NO MINIMUM QUANTITY

Size	Thickness	Material	Edge Finish	Wear Layer	Joint System	Packing Content	Area Suitability
150mm x 600mm	4mm	100% Virgin Material	Micro Bevel	12 MIL (0.3MM) + UV Coating	Interlocking Unilin Click	24 sqft/ 24 pcs/box	Indoor residential up to heavy commercial area



[CLICK HERE TO WATCH VIDEO](#)



CHEVRON HERRINGBONE 4MM



LUXURY SPC FLOORING

WEAR LAYER 12 MIL (0.3MM)



HARGA DIRECT KILANG 24 PCS / BOX @ 24 SQFT

RM2.88
/sqft

HARGA SIAP PASANG
RM4.45
MINIMUM 800 SQFT

RM4.78
MINIMUM 350 SQFT


RM69
(RM2.88/SQFT)
MINIMUM 100 BOX

RM74
(RM3.08/SQFT)
MINIMUM 50 BOX


RM79
(RM3.28/SQFT)
NO MINIMUM QUANTITY




HB009



HB005



HB004



HB006



HB002

[CLICK HERE TO WATCH VIDEO](#)





HB001

CHEVRON HERRINGBONE 4MM



LUXURY SPC FLOORING

WEAR LAYER 12 MIL (0.3MM)



COMMERCIAL



RESIDENTIAL

HARGA DIRECT KILANG

RM2.88
/sqft

HARGA SIAP PASANG

RM4.45
MINIMUM 800 SQFT

RM4.78
MINIMUM 350 SQFT

24 PCS / BOX @ 24 SQFT

RM69
(RM2.88/SQFT)
MINIMUM 100 BOX

RM74
(RM3.08/SQFT)
MINIMUM 50 BOX

RM79
(RM3.28/SQFT)
NO MINIMUM QUANTITY



HB007



HB009

CHEVRON HERRINGBONE 4MM



LUXURY SPC FLOORING

WEAR LAYER 12 MIL (0.3MM)



COMMERCIAL



RESIDENTIAL

HARGA DIRECT KILANG

RM2.88
/sqft

HARGA SIAP PASANG

RM4.45
MINIMUM 800 SQFT

RM4.78
MINIMUM 350 SQFT

24 PCS / BOX @ 24 SQFT

RM69
(RM2.88/SQFT)
MINIMUM 100 BOX

RM74
(RM3.08/SQFT)
MINIMUM 50 BOX

RM79
(RM3.28/SQFT)
NO MINIMUM QUANTITY



HB005



HB006


 <p>CHEVRON HERRINGBONE 4MM LUXURY SPC FLOORING WEAR LAYER 12 MIL (0.3MM)</p>	<p>HARGA DIRECT KILANG</p> <p>RM2.88 /sqft</p>	<p>24 PCS / BOX @ 24 SQFT</p> <p>RM69 (RM2.88/SQFT) MINIMUM 100 BOX</p>
	<p>HARGA SIAP PASANG</p> <p>RM4.45 MINIMUM 800 SQFT</p>	<p>RM74 (RM3.08/SQFT) MINIMUM 50 BOX</p>
	<p>RM4.78 MINIMUM 350 SQFT</p>	<p>RM79 (RM3.28/SQFT) NO MINIMUM QUANTITY</p>



10 YEAR WARRANTY
COMMERCIAL



15 YEAR WARRANTY
RESIDENTIAL



HB002



HB010

 <p>CHEVRON HERRINGBONE 4MM LUXURY SPC FLOORING WEAR LAYER 12 MIL (0.3MM)</p> <p>   COMMERCIAL RESIDENTIAL </p>	<p>HARGA DIRECT KILANG 24 PCS / BOX @ 24 SQFT</p> <p>RM2.88 /sqft</p>	<p>RM69 (RM2.88/SQFT) MINIMUM 100 BOX</p>
	<p>HARGA SIAP PASANG</p> <p>RM4.45 MINIMUM 800 SQFT</p>	<p>RM74 (RM3.08/SQFT) MINIMUM 50 BOX</p>
	<p>RM4.78 MINIMUM 350 SQFT</p>	<p>RM79 (RM3.28/SQFT) NO MINIMUM QUANTITY</p>



HB003



HB008

CHEVRON HERRINGBONE 4MM



LUXURY SPC FLOORING

WEAR LAYER 12 MIL (0.3MM)



COMMERCIAL



RESIDENTIAL

HARGA DIRECT KILANG

RM2.88
/sqft

HARGA SIAP PASANG

RM4.45
MINIMUM 800 SQFT

RM4.78
MINIMUM 350 SQFT

24 PCS / BOX @ 24 SQFT

RM69
(RM2.88/SQFT)
MINIMUM 100 BOX

RM74
(RM3.08/SQFT)
MINIMUM 50 BOX

RM79
(RM3.28/SQFT)
NO MINIMUM QUANTITY



HB004

CHEVRON HERRINGBONE 4MM



LUXURY SPC FLOORING

WEAR LAYER 12 MIL (0.3MM)



HARGA DIRECT KILANG 24 PCS / BOX @ 24 SQFT

RM2.88
/sqft

HARGA SIAP PASANG

RM4.45
MINIMUM 800 SQFT


RM4.78
MINIMUM 350 SQFT

RM69
(RM2.88/SQFT)
MINIMUM 100 BOX

RM74
(RM3.08/SQFT)
MINIMUM 50 BOX

RM79
(RM3.28/SQFT)
NO MINIMUM QUANTITY

STRUCTURE DIAGRAM



4MM VIRGIN SPC INTERLOCKING FLOORING

SPC Flooring provides exceptional dimensional stability, superior performance, waterproofing, and impressive indentation resistance due to its high density - core



WATERPROOF



STAIN RESISTANT



TERMITE RESISTANT



NOISE RESISTANT



SCRATCH RESISTANT



FLAME RETARDANT



AFFORDABLE



VARIETY OF DESIGN OPTIONS



PET-FRIENDLY

CHEVRON HERRINGBONE 4MM



LUXURY SPC FLOORING

WEAR LAYER 12 MIL (0.3MM)



HARGA DIRECT KILANG 24 PCS / BOX @ 24 SQFT

RM2.88 /sqft

HARGA SIAP PASANG

RM4.45 MINIMUM 800 SQFT

RM4.78 MINIMUM 350 SQFT

RM69 (RM2.88/SQFT) MINIMUM 100 BOX


RM74 (RM3.08/SQFT) MINIMUM 50 BOX

RM79 (RM3.28/SQFT) NO MINIMUM QUANTITY

METHOD OF INSTALLATION


1. Build starting triangles

[CLICK HERE TO WATCH VIDEO](#)




Take B-strips and A-strips and position them as shown above.

Note! The number of strips varies depending on the width of the strips used.



Install the strips precisely and in the order indicated by the numbers on the strips. Carefully check the joints between the strips after every strip that is added.

Note! No protruding edge may be felt!



Cut the triangle according to the indicated red line. Depending on the kind of saw you use, it may be useful to dismantle the triangle before sawing.

Note! The excess (below the line) is to be saved for last row installation.

2. Measuring the room




Define the wall from where you intend to start the installation. Mark out the center of the room.


3. Calculating the number of triangles



Measure the distance between the two straight lines, originating from the corners of the strips.



Divide this number by two, and get the X measurement.




Drawing the installation line
Start from the center of the room. Parallel offset the line using the X measurement as distance.

$$\frac{L + X}{Y} = \text{Quantity}$$

Calculate the number of needed starting triangles with the formula to the left.
Note! Round up to the next full number.

4. Start installation




Lay out the triangles with their long side towards the starting wall. Align the center triangle top with the installation line.

Make sure the underlay material is installed beforehand and the installation line remains visible.

Note! Use expansion wedges for the expansion gap.

5. Finalising the start row



Now cut the distances C-D and E-F from the remaining triangle(s), and position them.

Note! In case you have calculated and built an uneven number of triangles, leave the outer two triangles aside. For the case that you have built an even number of triangles, lay one aside.



ROYAL SPC 5MM (WITH 1MM IXPE)

WEAR LAYER 20 MIL (0.5MM)



HARGA DIRECT KILANG 10 PCS / BOX @ 24 SQFT

RM2.99
/sqft

HARGA SIAP PASANG

RM4.29
MINIMUM 800 SQFT

RM4.79
MINIMUM 350 SQFT

RM72
(RM2.99/SQFT)
MINIMUM 100 BOX

RM77
(RM3.19/SQFT)
MINIMUM 50 BOX

RM82
(RM3.39/SQFT)
NO MINIMUM QUANTITY

Size	Thickness	Material	Edge Finish	Wear Layer	Joint System	Packing Content	Area Suitability
183mm x 1220mm	5mm	100% Virgin Material	Micro Bevel	20 MIL (0.5MM) + UV Coating	Interlocking Unilin Click	24 sqft/ 10 pcs/box	Indoor residential up to heavy commercial area



CP5427



CP5404



CP5431



CP5432



ROYAL SPC 5MM (WITH 1MM IXPE)

WEAR LAYER 20 MIL (0.5MM)



HARGA DIRECT KILANG 10 PCS / BOX @ 24 SQFT

RM2.99
/sqft

HARGA SIAP PASANG

RM4.29
MINIMUM 800 SQFT

RM4.79
MINIMUM 350 SQFT

RM72
(RM2.99/SQFT)
MINIMUM 100 BOX

RM77
(RM3.19/SQFT)
MINIMUM 50 BOX

RM82
(RM3.39/SQFT)
NO MINIMUM QUANTITY



ROYAL SPC 5MM (WITH 1MM IXPE)

WEAR LAYER 20 MIL (0.5MM)



HARGA DIRECT KILANG 10 PCS / BOX @ 24 SQFT

RM2.99
/sqft

HARGA SIAP PASANG

RM4.29
MINIMUM 800 SQFT

RM4.79
MINIMUM 350 SQFT

RM72
(RM2.99/SQFT)
MINIMUM 100 BOX

RM77
(RM3.19/SQFT)
MINIMUM 50 BOX

RM82
(RM3.39/SQFT)
NO MINIMUM QUANTITY



ROYAL SPC 5MM (WITH 1MM IXPE)

WEAR LAYER 20 MIL (0.5MM)



HARGA DIRECT KILANG 10 PCS / BOX @ 24 SQFT

RM2.99
/sqft

HARGA SIAP PASANG

RM4.29
MINIMUM 800 SQFT


RM4.79
MINIMUM 350 SQFT

RM72
(RM2.99/SQFT)
MINIMUM 100 BOX

RM77
(RM3.19/SQFT)
MINIMUM 50 BOX

RM82
(RM3.39/SQFT)
NO MINIMUM QUANTITY

STRUCTURE DIAGRAM



5MM VIRGIN SPC INTERLOCKING FLOORING

SPC Flooring provides exceptional dimensional stability, superior performance, waterproofing, and impressive indentation resistance due to its high density - core



WATERPROOF



STAIN
RESISTANT



TERMITE
RESISTANT



NOISE
RESISTANT



SCRATCH
RESISTANT



FLAME
RETARDANT



AFFORDABLE



VARIETY OF
DESIGN
OPTIONS



PET-
FRIENDLY

ROYAL SPC 5MM (WITH 1MM IXPE)

WEAR LAYER 20 MIL (0.5MM)



HARGA DIRECT KILANG 10 PCS / BOX @ 24 SQFT

RM2.99
/sqft

HARGA SIAP PASANG

RM4.29
MINIMUM 800 SQFT


RM4.79
MINIMUM 350 SQFT

RM72
(RM2.99/SQFT)
MINIMUM 100 BOX

RM77
(RM3.19/SQFT)
MINIMUM 50 BOX

RM82
(RM3.39/SQFT)
NO MINIMUM QUANTITY

METHOD OF INSTALLATION



SIZE

183MM X 1220MM

WEAR LAYER

20 MIL (0.5MM)

COVERAGE PER BOX

24 SQFT (10 PCS)

THICKNESS



[CLICK HERE TO WATCH VIDEO](#)



with IXPE Underlayment Backing





ROYAL SPC 5MM (WITH 1MM IXPE)

WEAR LAYER 20 MIL (0.5MM)



HARGA DIRECT KILANG 10 PCS / BOX @ 24 SQFT

RM2.99
/sqft

HARGA SIAP PASANG

RM4.29
MINIMUM 800 SQFT

RM4.79
MINIMUM 350 SQFT

RM72
(RM2.99/SQFT)
MINIMUM 100 BOX

RM77
(RM3.19/SQFT)
MINIMUM 50 BOX

RM82
(RM3.39/SQFT)
NO MINIMUM QUANTITY

PRODUCT DETAIL

Material	100% Virgin Material
Size	183mm x 1220mm
Thickness	5mm
Wear Layer	20 mil (0.5mm)
Treatment	UV Coating (Two Coats)
Click & Lock System	Unilin
Wear Resistant	24 sqft/10 pcs per box
Packaging	Group T
4 Side Edges	Micro Bevel
Martindale Abrasion Test	EN 16094 (MSR-B2)
Castor Wheel Resistant	BS EN iso 4918:2021 (PASS)
Impact Resistant	BS EN 13329:2016+A2:2021 Annex H (BIGBALL>1000MM)
Reaction To Fire Behavior	ASTM E648-194a (CLASS 1)
Slip Resistance	DIN 51130-2004 (R10)
Emission of Formaldehyde	DIN717-2 (NOT DETECTED)
Residual Vinyl Chloride Monomer	EN ISO 6401-2008 (<0.5 MG/L)
VOC Test	GB 18581-2020 (PASS)
Phthalate Test	EN 14372 (PASS)
Prohibited Heavy Metal	ICP-OES (PASS)



GRAND WOOD 5MM SPC CLICK

WEAR LAYER 20 MIL (0.5MM)



HARGA DIRECT KILANG 10 PCS / BOX @ 24 SQFT

RM3.29
/sqft

HARGA SIAP PASANG

RM4.69
MINIMUM 800 SQFT

RM4.99
MINIMUM 350 SQFT

RM79
(RM3.29/SQFT)
MINIMUM 100 BOX

RM83
(RM3.49/SQFT)
MINIMUM 50 BOX

RM87
(RM3.69/SQFT)
NO MINIMUM QUANTITY

Size	Thickness	Material	Edge Finish	Wear Layer	Joint System	Packing Content	Area Suitability
183mm x 1220mm	5mm	100% Virgin Material	Micro Bevel	20 MIL (0.5MM) + UV Coating	Interlocking Unilin Click	24 sqft/ 10 pcs/box	Indoor residential up to heavy commercial area



CP536



CP504



CP528



CP505



CP521



CP517



CP527

[CLICK HERE TO WATCH VIDEO](#)





GRAND WOOD 5MM SPC CLICK

WEAR LAYER 20 MIL (0.5MM)



HARGA DIRECT KILANG 10 PCS / BOX @ 24 SQFT

RM3.29
/sqft

HARGA SIAP PASANG

RM4.69
MINIMUM 800 SQFT

RM4.99
MINIMUM 350 SQFT

RM79
(RM3.29/SQFT)
MINIMUM 100 BOX

RM83
(RM3.49/SQFT)
MINIMUM 50 BOX

RM87
(RM3.69/SQFT)
NO MINIMUM QUANTITY



CP529



CP537




CP532



CP514



CP533



CP535



CP534



CP531



CP501A



CP501B



CP502A



CP502B



CP518



CP520



CP530



CP516

[CLICK HERE TO WATCH VIDEO](#)



GRAND WOOD 5MM SPC CLICK

WEAR LAYER 20 MIL (0.5MM)



HARGA DIRECT KILANG

10 PCS / BOX @ 24 SQFT

RM3.29
/sqft

HARGA SIAP PASANG

RM4.69
MINIMUM 800 SQFT


RM4.99
MINIMUM 350 SQFT

RM79
(RM3.29/SQFT)
MINIMUM 100 BOX

RM83
(RM3.49/SQFT)
MINIMUM 50 BOX

RM87
(RM3.69/SQFT)
NO MINIMUM QUANTITY

STUCTURE DIAGRAM



5MM VIRGIN SPC INTERLOCKING FLOORING

SPC Flooring provides exceptional dimensional stability, superior performance, waterproofing, and impressive indentation resistance due to its high density - core



WATERPROOF

STAIN
RESISTANT

TERMITE
RESISTANT

NOISE
RESISTANT

SCRATCH
RESISTANT

FLAME
RETARDANT

AFFORDABLE


VARIETY OF
DESIGN
OPTIONS

PET-
FRIENDLY



GRAND WOOD 5MM SPC CLICK

WEAR LAYER 20 MIL (0.5MM)



HARGA DIRECT KILANG

10 PCS / BOX @ 24 SQFT

RM3.29
/sqft

HARGA SIAP PASANG

RM4.69
MINIMUM 800 SQFT


RM4.99
MINIMUM 350 SQFT

RM79
(RM3.29/SQFT)
MINIMUM 100 BOX

RM83
(RM3.49/SQFT)
MINIMUM 50 BOX

RM87
(RM3.69/SQFT)
NO MINIMUM QUANTITY

METHOD OF INSTALLATION



SIZE

183MM X 1220MM

WEAR LAYER

20 MIL (0.5MM)

COVERAGE PER BOX

24 SQFT (10 PCS)

THICKNESS



[CLICK HERE TO WATCH VIDEO](#)

VERIFIED BY :





GRAND WOOD 5MM SPC CLICK

WEAR LAYER 20 MIL (0.5MM)



HARGA DIRECT KILANG

RM3.29
/sqft

HARGA SIAP PASANG

RM4.69
MINIMUM 800 SQFT

RM4.99
MINIMUM 350 SQFT

10 PCS / BOX @ 24 SQFT

RM79
(RM3.29/SQFT)
MINIMUM 100 BOX

RM83
(RM3.49/SQFT)
MINIMUM 50 BOX

RM87
(RM3.69/SQFT)
NO MINIMUM QUANTITY

PRODUCT DETAIL

Material	100% Virgin Material
Size	183mm x 1220mm
Thickness	5mm
Wear Layer	20 mil (0.5mm)
Treatment	UV Coating (Two Coats)
Click & Lock System	Unilin
Wear Resistant	24 sqft/10 pcs per box
Packaging	Group T
4 Side Edges	Micro Bevel
Martindale Abrasion Test	EN 16094 (MSR-B2)
Castor Wheel Resistant	BS EN iso 4918:2021 (PASS)
Impact Resistant	BS EN 13329:2016+A2:2021 Annex H (BIGBALL>1000MM)
Reaction To Fire Behavior	ASTM E648-194a (CLASS 1)
Slip Resistance	DIN 51130-2004 (R10)
Emission of Formaldehyde	DIN717-2 (NOT DETECTED)
Residual Vinyl Chloride Monomer	EN ISO 6401-2008 (<0.5 MG/L)
VOC Test	GB 18581-2020 (PASS)
Phthalate Test	EN 14372 (PASS)
Prohibited Heavy Metal	ICP-OES (PASS)



EMPIRE 7MM VIRGIN SPC

WITH IXPE INTERLOCKING FLOORING
WEAR LAYER 20 MIL (0.5MM)



HARGA DIRECT KILANG 10 PCS / BOX @ 24 SQFT

RM4.30
/sqft

HARGA SIAP PASANG

RM5.50
MINIMUM 800 SQFT

RM5.80
MINIMUM 350 SQFT

RM103
(RM4.30/SQFT)
MINIMUM 100 BOX

RM108
(RM4.50/SQFT)
MINIMUM 50 BOX

RM113
(RM4.70/SQFT)
NO MINIMUM QUANTITY



CP729



CP730



CP731



CP732



CP733



CP734



CP735



CP736



CP737




[CLICK HERE TO WATCH VIDEO](#)



EMPIRE 7MM VIRGIN SPC

WITH IXPE INTERLOCKING FLOORING
WEAR LAYER 20 MIL (0.5MM)



HARGA DIRECT KILANG 10 PCS / BOX @ 24 SQFT

RM4.30
/sqft

HARGA SIAP PASANG

RM5.50
MINIMUM 800 SQFT

RM5.80
MINIMUM 350 SQFT

RM103
(RM4.30/SQFT)
MINIMUM 100 BOX

RM108
(RM4.50/SQFT)
MINIMUM 50 BOX

RM113
(RM4.70/SQFT)
NO MINIMUM QUANTITY

Size	Thickness	Material	Edge Finish	Wear Layer	Joint System	Packing Content	Area Suitability
183mm x 1220mm	7mm	100% Virgin Material	Micro Bevel	20 MIL (0.5MM) + UV Coating	Interlocking Unilin Click	24 sqft/ 10 pcs/box	Indoor residential up to heavy commercial area



CP701A



CP701B



CP702A



CP702B



CP704



CP714



CP705



CP716



CP717



CP718



CP721



CP727



CP720



CP728





EMPIRE 7MM VIRGIN SPC

WITH IXPE INTERLOCKING FLOORING
WEAR LAYER 20 MIL (0.5MM)



HARGA DIRECT KILANG 10 PCS / BOX @ 24 SQFT

RM4.30
/sqft

HARGA SIAP PASANG

RM5.50
MINIMUM 800 SQFT


RM5.80
MINIMUM 350 SQFT

RM103
(RM4.30/SQFT)
MINIMUM 100 BOX

RM108
(RM4.50/SQFT)
MINIMUM 50 BOX

RM113
(RM4.70/SQFT)
NO MINIMUM QUANTITY

STRUCTURE DIAGRAM



SPECIAL GRADE UV TREATED LAYER

OUTSTANDING DURABILITY & EASY TO CARE FOR. THE TOP LAYER THAT PREVENTS THE INNER LAYERS FROM DAMAGE AND SCRATCHES.

HIGH DENSITY RESISTANT WEAR LAYER

THE CARE PROTECTION FILM FOR THE LONG LIFE

PRINTING FILM

PIXELIS OVER 300 MILLION, TAKE FROM THE REAL VARIOUS TETURE

RIGID CORE

SUPPORT THE BALANCE OF THE FLOOR STRUCTURE HAS GOOD FIRE-RETARDAND

SHOCK ABSORPTION UNDERLAYMENT IXPE

EVEN ON THE SHOCK ABSORPTION IS MAINLY AFFECTED BY SUB OOR MATARIAL RATHER THEN OOR COVERING.

7MM VIRGIN SPC INTERLOCKING FLOORING

SPC Flooring provides exceptional dimensional stability, superior performance, waterproofing, and impressive indentation resistance due to its high density - core



WATERPROOF

STAIN
RESISTANT

TERMITE
RESISTANT

NOISE
RESISTANT

SCRATCH
RESISTANT

FLAME
RETARDANT

AFFORDABLE


VARIETY OF
DESIGN
OPTIONS

PET-
FRIENDLY



EMPIRE 7MM VIRGIN SPC

WITH IXPE INTERLOCKING FLOORING
WEAR LAYER 20 MIL (0.5MM)



HARGA DIRECT KILANG 10 PCS / BOX @ 24 SQFT

RM4.30
/sqft

RM103
(RM4.30/SQFT)
MINIMUM 100 BOX

HARGA SIAP PASANG


RM5.50
MINIMUM 800 SQFT

RM108
(RM4.50/SQFT)
MINIMUM 50 BOX

RM5.80
MINIMUM 350 SQFT

RM113
(RM4.70/SQFT)
NO MINIMUM QUANTITY

METHOD OF INSTALLATION



SIZE

183MM X 1220MM

[CLICK HERE TO WATCH VIDEO](#)

WEAR LAYER

20MIL (0.5MM)

COVERAGE PER BOX

24 SQFT (10 PCS)

THICKNESS

7MM

VERIFIED BY :



with IXPE Underlayment Backing



EMPIRE 7MM VIRGIN SPC

WITH IXPE INTERLOCKING FLOORING
WEAR LAYER 20 MIL (0.5MM)



HARGA DIRECT KILANG

RM4.30
/sqft

HARGA SIAP PASANG

RM5.50
MINIMUM 800 SQFT

RM5.80
MINIMUM 350 SQFT

10 PCS / BOX @ 24 SQFT

RM103
(RM4.30/SQFT)
MINIMUM 100 BOX

RM108
(RM4.50/SQFT)
MINIMUM 50 BOX

RM113
(RM4.70/SQFT)
NO MINIMUM QUANTITY

PRODUCT DETAIL

Material	100% Virgin Material
Size	183mm x 1220mm
Thickness	7mm
Wear Layer	20 mil (0.5mm)
Treatment	UV Coating (Two Coats)
Click & Lock System	Unilin
Wear Resistant	24 sqft/10 pcs per box
Packaging	Group T
4 Side Edges	Micro Bevel
Martindale Abrasion Test	EN 16094 (MSR-B2)
Castor Wheel Resistant	BS EN iso 4918:2021 (PASS)
Impact Resistant	BS EN 13329:2016+A2:2021 Annex H (BIGBALL>1000MM)
Reaction To Fire Behavior	ASTM E648-194a (CLASS 1)
Slip Resistance	DIN 51130-2004 (R10)
Emission of Formaldehyde	DIN717-2 (NOT DETECTED)
Residual Vinyl Chloride Monomer	EN ISO 6401-2008 (<0.5 MG/L)
VOC Test	GB 18581-2020 (PASS)
Phthalate Test	EN 14372 (PASS)
Prohibited Heavy Metal	ICP-OES (PASS)



FLOORING ACCESSORIES

Skirting & Profile Application



Adaptation (A-profile)

To transition new floor to existing floor that is different in height. This is used when you have two area with new and existing floor.



Stairnose (SN-profile) and L-profile

L profile is for flooring at staircase, doorway, entrance (with step up). This is to close the connection edges between floorboards.



End (N-profile)

To close the gap around corner such as around cabinet and sliding door. Install all around walls (when existing skirtings are not removed).

SN-profile functions the same as L profile, is to cover connection. Protect feet from injury.

Available rounded edges and L-shape for different flooring thickness.



Transition (T-profile)

Connecting two areas with same height flooring and hiding the expansion gap in between. Comes with a PVC track, glue it down and snap the profile on it.



Skirting

To cover the expansion gap around all sides of walls with matching colour, protect from damage such as scratches & knocks by foot traffic or furniture.

PVC SKIRTING 70MM


Product Description

Product : Skirting 70mm

Type : PVC

Specification :

12mm x 70mm x 2400mm



PURE WHITE



PURE BLACK



MATT WHITE



LATTE



BEIGE



MAPLE



GREY



TEAK



DARK WALNUT

HARGA DIRECT KILANG

12.00/ pcs

HARGA SIAP PASANG

22.00/ pcs



FLOORING ACCESSORIES




70 MM SPC SKIRTING

SPECTIFICATION

Thickness : 15mm

Size : L 2400mm X H 70mm X D 15mm

HARGA DIRECT KILANG
RM12.00/PCS
HARGA SIAP PASANG
RM22.00/PCS



705




704




706



702



703



701




100 MM SPC SKIRTING

SPECTIFICATION

Thickness : 15mm

Size : L 2400mm X H 100mm X D 15mm

HARGA DIRECT KILANG
RM14.00/PCS
HARGA SIAP PASANG
RM24.00/PCS



1001



1002



1003



1004



1005



1006




1007



1008



1009



1010




1011



FLOORING ACCESSORIES



HARGA DIRECT KILANG
RM **14.20** /PCS
HARGA SIAP PASANG
RM **24.20** /PCS





SPC A-PROFILE (ADAPTATION)


SPECIFICATION

Thickness : 15mm

Size : L 2700mm x H 7mm X D 25mm



HARGA DIRECT KILANG
RM **13.00** /PCS
HARGA SIAP PASANG
RM **23.00** /PCS



SPC T - PROFILE JOINT


SPECIFICATION

Thickness : 5mm

Size : L 2700mm x H 5mm X D 25mm



HARGA DIRECT KILANG
RM **12.70** /PCS
HARGA SIAP PASANG
RM **22.70** /PCS



SPC L-PROFILE

SPECIFICATION

Thickness : 20mm

Size : L 2700mm x H 20mm X D 30mm



SKIRTING & PROFILE PURPOSE

In floor installation, **SKIRTING** serve important purpose.

Aesthetic Enhancement

Skirting serves as a stylish and practical finishing detail, covering the joint between the floor and the wall. Available in a wide range of colors and designs, it complements various interior styles and architectural themes, enhancing the overall appearance of any space. Beyond its visual appeal, skirting also provides essential protection, safeguarding walls from damage caused by foot traffic, furniture, and routine cleaning, while ensuring long-term durability and maintenance ease.

Protection

Skirting helps protect the bottom of the wall from damage caused by furniture, foot traffic, and cleaning equipment like vacuum cleaners. Without skirting, walls are more vulnerable to scuff marks, scratches, and dents. It acts as a protective barrier, absorbing impacts and preventing direct contact with the wall.

Concealing Imperfections

Skirting effectively hides imperfections in the flooring installation, such as gaps, uneven edges, or expansion joints. It creates a smooth transition between the floor and the wall, offering a cleaner, more polished appearance while masking any installation flaws.



In floor installation, **PROFILES** serve important purpose.

Transition

Profiles provide smooth transitions between different flooring materials, such as tile to hardwood, carpet to tile, or laminate to vinyl. They ensure a seamless flow between rooms with varying flooring types, enhancing the overall aesthetic and creating a cohesive look throughout the space.

Protection

Profiles protect the edges of flooring from damage caused by foot traffic, furniture, and general wear. They help prevent chipping, cracking, and splintering, thereby extending the life of the flooring and maintaining its appearance over time.

Safety

Certain profiles, such as stairnose profiles, enhance safety by reducing the risk of slips and falls on stairs. They create defined edges on each step, improving traction and visibility, especially in high-traffic areas.

Expansion Gaps

Profiles, including expansion joint profiles, allow for the natural expansion and contraction of flooring materials due to changes in temperature and humidity. This helps prevent buckling, warping, and structural damage by accommodating movement without restriction.

Aesthetic Enhancement

Available in a range of styles and colors, profiles complement the overall design of a space. They add a decorative element to the flooring installation, enhancing the visual appeal and contributing to a polished, cohesive look.





HARGA PEMASANGAN

RM **2.00**/sqft
(above 5000 sqft)

RM **2.50**/sqft
(1000 to 5000 sqft)

RM **3.00**/sqft
(minimum 300 sqft)

SUB-FLOOR PREPARATION SELF-LEVELLING (If Required)

We only use Top Class Mapei Brand Novoplan & Ultraplan



Self-levelling compound, also known as floor screed or floor levelling compound, is a critical material used to create a flat and even subfloor in preparation for the installation of upper flooring layers. It is designed to be applied over a range of uneven substrates, utilizing gravity to spread and self-level the latex-based mixture. Self-levelling compound is particularly recommended for vinyl and SPC flooring installations, especially for floors less than 5mm in thickness, when the subfloor is not perfectly level. It helps prevent visual imperfections, such as a wavy appearance, ensuring a smooth, professional finish and enhancing the overall aesthetic quality of the flooring.



UNDERLAY FOR SPC



RM35/ROLL@1MX50M

**MOISTURE BARRIER SHEET
(540 SQFT/ROLL)**

7 SEN /SQFT



1MM PE FOAM

6 SEN /SQFT



2 MM PE FOAM

10 SEN /SQFT



2MM PE FOAM WITH SILVER FOIL

20 SEN /SQFT



VITECH VT-226 GP GAP SEALANT/PAINTANLE (350G)

RM3.75



VITECH VT-230 NAILS SEALANT (350G)

RM6.88



NOVO PLAN MAPEI

RM49



ULTRA PLAN MAPEI

RM51



PRIMER G

**RM75/ 5KG
RM364/ 25KG**



FLOATING INSTALLATION GUIDE



- 1** Clean the sub-floor
Bersihkan lantai asal



- 2** Lay moisture barrier sheet
Letakkan plastik penghalang kelembapan



- 3** Lay underlayment
Letakkan lapisan foam



- 4** Install flooring
Pasang lantai



- 5** Create expansion gap
Pastikan ada jurang pengembang



- 6** Cover expansion gap with skirting/N-profile
Tutup jurang pengembang dengan skirting/profil-N



- 7** Cover doorway expansion gap with T-profile/A-profile
Tutup celah pengembangan pintu dengan profil-T/profil-A



- 8** Protect the installed flooring if there are still other ongoing renovation works
Lindungi lantai yang dipasang jika masih terdapat kerja-kerja pengubahsuaian lain yang sedang dijalankan



DELIVERS THE ULTIMATES PERFORMANCE

✔ **FUNCTIONALITY** – Floorboard Type ✔ **STABILITY** – Floorboard Thickness ✔ **DURABILITY** – Wear Layer Thickness



WATERPROOF FLOORING TYPE PERFORMANCE OVERVIEW

5 4 3 2 1
EXCELLENT GOOD AVERAGE ACCEPTABLE POOR

PRODUCT	WATERPROOF	MOISTURE PROOF	TERMITE RESISTANT	HEAT RESISTANT	SCRATCH RESISTANT	STAIN RESISTANT	CUPPING RESISTANT	IMPACT RESISTANT	WOOD FEEL
SPC	5	5	5	5	5	5	4	5	5
PVC	5	3	5	3	4	4	4	4	3

Stone Plastic Composite (SPC) - SPC Flooring Polyvinyl Chloride (PVC) - Vinyl Flooring

FLOORBOARD THICKNESS STABILITY PERFORMANCE (SPC & VINYL)

FLOORBOARD THICKNESS	AREA SIZE (5X10M)	AREA SIZE (10X20M)	AREA SIZE (20X30M)
< 4MM	SUITABLE	SUITABLE	-
5MM - 7MM	SUITABLE	SUITABLE	SUITABLE

Note 1: Suitable for continuous floating install up to xx area size before separation by transition profile is required to avoid warping.

Note 2: Only ULTRAWOOD 12mm is suitable for continuous floating install up to 20x30m & all vinyl flooring adopted glue down installation method.

WEAR LAYER THICKNESS DURABILITY PERFORMANCE (SPC & VINYL)

WEAR LAYER THICKNESS	RESIDENTIAL	COMMERCIAL		
	ALL	LIGH	MEDERATE	HEAVY
4 MIL (0.1MM) AC1 ☆	SUITABLE	SUITABLE	SUITABLE	-
12 MIL (0.3MM) AC2 ☆☆	SUITABLE	SUITABLE	SUITABLE	SUITABLE
20 MIL (0.5MM) AC3 ☆☆☆	SUITABLE	SUITABLE	SUITABLE	SUITABLE

Note: Wear layer durability for SPC & Vinyl is measure by number of years the flooring surface wear layer will totally worn out under normal usage condition.